

Datasheet for #sbcw6200 DN

Recommendations:

Please read the User Manual and have a look at the FAQ at
<http://www.alpeslasers.ch/?a=142>

WARNING: Operating the laser with higher current or voltage than specified in this document may cause damage and will result in loss of warranty, unless Alpes Lasers has permitted to do so!

WARNING: Beware of the polarity of the laser. This laser has to be powered with negative current on the laser contact (= bonding pad, corresponding to the label "laser" on the LLH) and the positive current on the base contact (= submount, corresponding to the label "base" on the LLH). To use with a power-supply ILX Lightwave LDX-3232 or equivalent.



Figure 1: Mechanical and electrical interface for #sbcw6200 DN




Figure 2: Output power as a function of the singlemode emission frequencies and temperatures




Figure 3: Applied DC current as a function of singlemode emission frequencies and temperatures

λ [nm]	ν [cm $^{-1}$]	P[mW]	Temp[°C]	U_{LASER} [V]	I[A]
12107.8	825.9	10	-10	10.1	1.07
12130.5	824.4	0.3	0	9.7	1.02
12140.8	823.7	9.8	0	10.3	1.17
12143.5	823.5	0.5	10	9.8	1.09
12148.9	823.1	4.8	10	10.1	1.16
12156.7	822.6	9.2	10	10.5	1.26
12158	822.5	0.5	20	9.9	1.17
12165.1	822	4.5	20	10.2	1.26
12173.5	821.5	7.3	20	10.6	1.36
12173.7	821.4	0.5	30	10	1.27
12182.2	820.9	3.2	30	10.4	1.36
12496.1	800.2	0.7	-10	9.5	0.95

Table 1: Singlemode optical output power as function of operating parameters.




Figure 4: voltage and avg power vs current in continuous-wave operation (the solid squares indicate the maximum singlemode emitted power)





Figure 5: voltage and avg power vs current in continuous-wave operation (including the multimode region)

Note: at -20C: $I_{th}=0.86A$ / $V_{th}=9.85V$ (2-wires measurements). Maximum operation current: 1.1A at -20C and -10C, 1.17A at 0C, 1.27A at 10C, 1.37A at 20C and 30C.

Figure 4: spectra at different temperatures for various DC currents






Figure 6: spectra at -20C for various DC currents (bimode)




Figure 7: spectra at -10C for various DC currents (monomode on mode 1 up to 0.95A, then becomes monomode on mode 2)

Figure 7: spectra between 0C and 30C for various DC currents (all monomode on mode 2)

