

# EYP-DBR-0633-00010-2000-BFW01-0000


Revision 0.74

2017-07-05

## SINGLE FREQUENCY LASER DIODES Distributed Bragg Reflector Laser

### General Product Information

Product	Application
633 nm DBR Laser	HeNe Laser Replacement
with hermetic 14-Pin Butterfly Housing (RoHS compliant)	Spectroscopy, Metrology, Sensing
including Monitor Diode, Thermoelectric Cooler and Thermistor	Please note: The use of the laser in
Collimated beam	3D trackers is protected by patents



### Absolute Maximum Ratings

Parameter	Symbol	Unit	min	typ	max
Storage Temperature	$T_S$	°C	-40		85
Operational Temperature at Case	$T_C$	°C	-20		75
Operational Temperature at Laser Chip	$T_{LD}$	°C	-5		25
Forward Current	$I_F$	mA			180
Reverse Voltage	$V_R$	V			2
Output Power	$P_{opt}$	mW			12
TEC Current	$I_{TEC}$	A			1.1
TEC Voltage	$V_{TEC}$	V			2.8

### Measurement Conditions / Comments

Stress in excess of one of the Absolute Maximum Ratings may damage the laser. Please note that a damaging optical power level may occur although the maximum current is not reached. These are stress ratings only, and functional operation at these or any other conditions beyond those indicated under Recommended Operational Conditions is not implied.

### Recommended Operational Conditions

Parameter	Symbol	Unit	min	typ	max
Operational Temperature at Case	$T_{case}$	°C	0		50
Operational Temperature at Laser Chip	$T_{LD}$	°C	10		18
Forward Current	$I_F$	mA		100	160
Output Power	$P_{opt}$	mW			10

### Measurement Conditions / Comments

measured by integrated Thermistor

### Characteristics at $T_{LD} = 15^\circ$ at BOL

Parameter	Symbol	Unit	min	typ	max
Center Wavelength	$\lambda_c$	nm	632	633	634
Linewidth (FWHM)	$\Delta\lambda$	MHz		1	
Sidemode Suppression Ratio	SMSR	dB	30		
Temperature Coefficient of Wavelength	$d\lambda / dT$	nm / K		0.045	
Current Coefficient of Wavelength	$d\lambda / dI$	nm / mA		0.001	

### Measurement Conditions / Comments

$P_{opt} = 10$  mW

# EYP-DBR-0633-00010-2000-BFW01-0000

Revision 0.74

2017-07-05

## SINGLE FREQUENCY LASER DIODES Distributed Bragg Reflector Laser



### Characteristics at $T_{LD} = 15^\circ$ at BOL cont'd

Parameter	Symbol	Unit	min	typ	max
Laser Current @ $P_{opt} = 10$ mW	$I_{LD}$	mA			160
Slope Efficiency	$\eta$	W / A	0.1	0.4	0.7
Threshold Current	$I_{th}$	mA		80	120
Divergence parallel (FWHM)	$\Theta_{  }$	°		0.1	
Divergence perpendicular (FWHM)	$\Theta_{\perp}$	°		0.1	
Beam Diameter horizontal ( $1/e^2$ )	$d_{  }$	mm		0.7	1.0
Beam Diameter vertical ( $1/e^2$ )	$d_{\perp}$	mm		0.6	1.0
Degree of Polarization	DOP	%		90	

#### Measurement Conditions / Comments

lth drift may occur, no violation of the max. value  
parallel to the base plate of the housing (see p. 3)  
perpendicular to base plate of the housing (see p. 3)  
parallel to the base plate of the housing (see p. 3)  
perpendicular to base plate of the housing (see p. 3)  
 $P_{opt} = 10$  mW; E field perpendicular to base plate

### Monitor Diode

Parameter	Symbol	Unit	min	typ	max
Monitor Detector Responsivity	$I_{mon} / P_{opt}$	$\mu$ A/mW	10		400

#### Measurement Conditions / Comments

$U_R = 5$  V

### Thermoelectric Cooler

Parameter	Symbol	Unit	min	typ	max
Current	$I_{TEC}$	A		0.7	1.1
Voltage	$U_{TEC}$	V		1.7	2.8
Power Dissipation (total loss at case)	$P_{loss}$	W		0.4	0.5
Temperature Difference	$\Delta T$	K			60

#### Measurement Conditions / Comments

$P_{opt} = 10$  mW,  $\Delta T = 40$  K

$P_{opt} = 10$  mW,  $\Delta T = 40$  K

$P_{opt} = 10$  mW,  $\Delta T = 40$  K

$P_{opt} = 10$  mW,  $\Delta T = |T_{case} - T_{LD}|$

### Thermistor (Standard NTC Type)

Parameter	Symbol	Unit	min	typ	max
Resistance	R	k $\Omega$		10	
Beta Coefficient	$\beta$			3892	
Steinhart & Hart Coefficient A	A			$1.1293 \times 10^{-3}$	
Steinhart & Hart Coefficient B	B			$2.3410 \times 10^{-4}$	
Steinhart & Hart Coefficient C	C			$8.7755 \times 10^{-8}$	

#### Measurement Conditions / Comments

$T_{LD} = 25^\circ$  C

$R_1 / R_2 = e^{\beta(1/T_1 - 1/T_2)}$  at  $T_{LD} = 0^\circ \dots 50^\circ$  C

$1/T = A + B(\ln R) + C(\ln R)^3$

T: temperature in Kelvin

R: resistance at T in Ohm

# EYP-DBR-0633-00010-2000-BFW01-0000

Revision 0.74


2017-07-05

## SINGLE FREQUENCY LASER DIODES Distributed Bragg Reflector Laser



### Pin Assignment

1	Thermoelectric Cooler (+)	14	Thermoelectric Cooler (-)
2	Thermistor	13	Case
3	Photodiode (Anode)	12	not connected
4	Photodiode (Cathode)	11	Laser Diode (Cathode)
5	Thermistor	10	Laser Diode (Anode)
6	not connected	9	not connected
7	not connected	8	not connected


All 14 pins are isolated from case.



### Package Drawings



AIZ-15-0729-0947



# EYP-DBR-0633-00010-2000-BFW01-0000


Revision 0.74

2017-07-05


## SINGLE FREQUENCY LASER DIODES Distributed Bragg Reflector Laser

### Typical Measurement Results

Output Power vs. Current



Spectra at Specified Optical Output Power



Performance figures, data and any illustrative material provided in this specification are typical and must be specifically confirmed in writing by eagleyard Photonics before they become applicable to any particular order or contract. In accordance with the eagleyard Photonics policy of continuous improvement specifications may change without notice.

### Unpacking, Installation and Laser Safety

Unpacking the laser diodes should only be done at electrostatic safe workstations (EPA). Though protection against electro static discharge (ESD) is implemented in the laser package, charges may occur at surfaces. Please store this product in its original package at a dry, clean place until final use. During device installation, ESD protection has to be maintained.

The DBR laser is sensitive against optical feedback, so an optical isolator may be required in order to avoid any disturbance of the emission spectrum. Operating at moderate temperatures on proper heat sinks will contribute to a long lifetime of the diode.

Avoid direct and/or indirect exposure to the free running beam. Collimating and focussing the free running beam with optics as common in optical instruments will increase threat to the human eye.

Performance figures, data and any illustrative material provided in this specification are typical and must be specifically confirmed in writing by eagleyard Photonics before they become applicable to any particular order or contract. In accordance with the eagleyard Photonics policy of continuous improvement specifications may change without notice.

