

Terrestrial Laser Scanning

**NEW**



# RIEGL VZ-600i


Exceeding your expectations



[www.riegl.com](http://www.riegl.com)


# RIEGL VZ-600i<sup>®</sup>

RIEGL's latest generation of professional Terrestrial Laser Scanners stands for extreme versatility, high productivity, ultimate performance, and additional mobility – providing an excellent return on investment.



## High Productivity

- 60 scan positions per hour (with image acquisition)
- One-Touch button operation
- RIEGL VZ-i Project Map App for scan project monitoring
- simultaneous scan and image data acquisition
- Real-Time On-Board automatic registration
- One-Touch Processing Wizard in RiSCAN PRO for automatic production of detailed PDF-report




## Ultimate Performance

- broad range capability (0.5 m up to 1000 m)
- 5 sec scan time for low resolution overview scans
- 30 sec scan time for 6 mm resolution @ 10 m distance
- pulse repetition rate up to 2.2 MHz
- 3D position accuracy up to 3 mm @ 50 m
- scan speed up to 420 lines/sec
- high speed data download of up to 500 MB/sec



## Extreme Versatility

- for various applications
- indoor and outdoor 3D mapping
- internal cameras and GNSS receiver
- lightweight (approx. 6 kg / 13 lbs)
- prepared for user-specific Python apps



## Additional Mobility


- prepared for robotic operation (ROS driver available)
- option for mobile mapping
- can be used with the RIEGL VMR Robotic Rail Scanning System
- flexible mounting platforms

# Extreme Versatility – Key Applications

Key Applications




The new *RIEGL* VZ-600i is operable in a wide variety of applications, featuring reliable and robust automatic real-time on-board registration.



### BIM (Building Information Modeling)

High speed data acquisition, verifiably precise scan data, large projects (100s of scan positions), accuracy better than 10 mm for digital twins.




### Forestry and Vegetation

ToF (Time of Flight) measurement with multi-target responses, minimize occlusion, vegetation penetration, waveform.



### Public Safety and Forensics

Fast data capture to release scenes earlier, lightweight scanner for all staff, proven data for court presentation.



### Railroad Surveying

Robotic operation - use of onboard sensors and ROS for fast and repeatable data acquisition, railway applications with the *RIEGL* VMR Robotic Rail Laser Scanning System.

### Construction

Inspection and varification for design build tilt wall/panel construction, blockouts & sleeves locations, and vertical wall plumbness. Ideal for preconstruction and large-scale ground grading and post roadway construction.


### Surveying and Mapping

Precise and accurate mapping of any environment for planning, design, and traditional survey. Streamline registration to survey control with full reporting in PDF format.

# High Productivity – Rapid Data Acquisition




## 1<sup>st</sup> Scan Position



RIEGL VZ-600i Screen or VZ-i Series App

## 66<sup>th</sup> Scan Position




RIEGL VZ-600i Screen or VZ-i Series App




### Key Features of rapid data acquisition with the RIEGL VZ-600i:

- up to 60 scan positions per hour
- 6 mm resolution @ 10 m distance
- simultaneous image acquisition
- real-time on-board automatic registration, no tablet required
- no tie points necessary for robust registration
- remote control by the use of the RIEGL VZ-i Series App (for iOS and Android)
- monitor registration with the VZ-i Project Map App (direct from the scanner)




VZ-i Project Map App



VZ-i Project Map App

# High Productivity – Swift Data Processing

Produce end deliverables with the Data Processing Software RiSCAN PRO and its One-Touch Processing Wizard.




RiSCAN PRO – One-Touch Processing Wizard

## Key Features of the Data Processing Software RiSCAN PRO:


- One-Touch Processing Wizard
- fast download from the CF-Express Card (up to 500 MB/sec)
- automatic filtering (e.g. dynamic objects, deviation, reflectance, multiple targets, etc.)
- optimization of the camera mounting calibration
- automatic colorization of the point cloud
- generation of ortho plots (e.g. GeoTIFF)
- export as RiPANO project, e57 project, LAS, etc.
- automatic generation of PDF report



PDF report



Floor plan, all floors



Floor plan, one floor



3D Point Cloud

# Key Components

Front View

Rear View



# Optional Equipment



## RTK GNSS antenna and/or external camera

With an attached RTK-GNSS antenna, the absolute positioning accuracy can be improved to 1-2 cm. The correction data is then received via WLAN.

## Charger for 2 or 6 batteries




The chargers are designed for 2 or 6 batteries. They can be supplied from the 12 V DC voltage of a vehicle as well as from a corresponding 110/230 V AC power supply module. The advantage of the 2-fold charger lies in the size and weight, that of the 6-fold charger in the possibility of continuous scanning over 24 hours (with simultaneous charging of the empty batteries).

## Optional Equipment



# Ultimate Performance – Technical Data

## Laser Product Classification

<b>Class 1 Laser Product according to IEC 60825-1:2014</b>	The following clause applies for instruments delivered into the United States: Complies with 21 CFR 1040.10 and 1040.11 except for conformance with IEC 60825-1 Ed.3., as described in Laser Notice No. 56, dated May 8, 2019.	
--	--	---

## Range Measurement Performance

<b>Measuring Principle / Mode of Operation</b>	time of flight measurement, echo signal digitization, online waveform processing			
<b>Laser Pulse Repetition Rate (PRR) – (peak) <sup>1)</sup></b>	<b>2200 kHz</b>	1200 kHz	600 kHz	140 kHz
<b>Max. Measuring Range <sup>2)</sup></b> natural targets $\rho \geq 90\%$ natural targets $\rho \geq 20\%$	<b>220 m</b> <b>100 m</b>	320 m 150 m	420 m 200 m	1000 m 450 m
<b>Minimum Range <sup>3)</sup></b>	<b>0.5 m</b>	0.5 m	0.5 m	1 m
<b>Max. Number of Targets per Pulse <sup>4)</sup></b>	<b>5</b>	10	15	15
<b>Ranging Accuracy <sup>5) 7)</sup></b>	<b>5 mm</b>			
<b>3D Position Accuracy <sup>8)</sup></b>	<b>3 mm @ 50 m, 5 mm @ 100 m</b>			
<b>Precision <sup>6) 7)</sup></b>	<b>3 mm</b> (1 mm with extended scan time and reduced maximum measuring range)			
<b>Laser Wavelength</b>	near infrared, invisible			
<b>Laser Beam Divergence</b>	0.35 mrad <sup>9)</sup> / 0.25 mrad <sup>10)</sup>			

- 1) Rounded values.
- 2) Typical values for average conditions. Maximum range is specified for flat targets with size in excess of the laser beam diameter, perpendicular angle of incidence, and for atmospheric visibility of 23 km. In bright sunlight, the max. range is shorter than under overcast sky.
- 3) Minimum range specified for vertical zenith angles from 25 deg to 130 deg, resp. 105° vertical field of view.
- 4) If more than one target is hit, the total laser transmitter power is split and, accordingly, the achievable range is reduced.
- 5) Accuracy is the degree of conformity of a measured quantity to its actual (true) value.
- 6) Precision, also called reproducibility or repeatability, is the degree to which further measurements show the same result.
- 7) 1 sigma @ 100 m range under RIEGL test conditions.
- 8) 1-sigma value, based on target modelling, under RIEGL test conditions.
- 9) Measured at the 1/e<sup>2</sup> points. 0.35 mrad corresponds to an increase of 35 mm of beam diameter per 100 m distance.
- 10) Measured at the 1/e points. 0.25 mrad corresponds to an increase of 25 mm of beam diameter per 100 m distance.

## Scanner Performance

	Vertical (Line) Scan	Horizontal (Frame) Scan
<b>Scan Angle Range</b>	total 105° (+65° / -40°)	max. 360°
<b>Scanning Mechanism</b>	rotating multi-facet mirror	rotating head
<b>Scan Speed</b>	4 lines/sec to 420 lines/sec	0°/sec to 360°/sec <sup>11)</sup>
<b>Performance</b>	<b>scan time less than 30 seconds for “Panorama_6mm”</b> (approx. 30 Mio measurements) 6 mm resolution @ 10 m distance, <b>up to 60 scan positions per hour</b> (including scan and image acquisition with real-time onboard registration)	
<b>Angular Step Width <sup>12)</sup></b> $\Delta\theta$ (vertical), $\Delta\phi$ (horizontal) <b>User defineable Resolution</b>	0.0007° ≤ $\Delta\theta$ ≤ 0.54° between consecutive laser shots	0.0015° ≤ $\Delta\phi$ ≤ 0.86° between consecutive scan lines
<b>Angular Accuracy <sup>13)</sup></b>	0.0028° (10 arcsec)	0.0028° (10 arcsec)
<b>Angle Measurement Resolution</b>	better 0.0007° (2.5 arcsec)	better 0.0005° (1.8 arcsec)

11) Frame scan can be disabled, providing 2D scanner operation.  
 12) Selectable.  
 13) 1-sigma value, based on target modeling, under RIEGL test conditions

Technical Data to be continued at page 8

## Scanner Performance (continued)

<b>Orientation Sensors</b>	integrated 3-axis accelerometer, 3-axis gyroscope, 3-axis magnetometer (compass), barometer
<b>GNSS Receiver</b>	integrated L1 GNSS receiver, optional external <i>RIEGL</i> GNSS RTK receiver
<b>Waveform Data Output (optional)</b>	providing digitized echo signal information for specific target echoes
<b>Data Storage</b>	integrated SSD 2 TByte, removable CF-Express card 512 GByte (1 TByte optionally available), automatic sync while scanning
<b>Cloud Storage</b>	Amazon S3, FTP-Server, Microsoft Azure
<b>On-board Registration</b>	automatic scan data registration as background process while scanning

## Scanner Control

<b>via Laser Scanner</b>	7 inch touch screen, 1280 pixel x 800 pixel
<b>via Mobile Device(WiFi)</b>	„ <i>RIEGL</i> VZi-Series“-App, available for iOS and Android
<b>via ROS</b>	ROS (Robot Operation System) driver available

## Camera

<b>Internal Camera</b> Anonymization of Image Data <sup>1)</sup>	3 x 12 MPix CMOS color cameras, FOV 115° x 40° (v x h) optional on-board face detection and automatic facial blurring in real time before image storage
<b>External Camera (optional)</b>	detachable SONY α7R IV
<b>Panorama Camera (optional)</b>	detachable RICOH Theta Z1

1) To comply with the requirements of the European General Data Protection Regulation (GDPR), among others.

## General Technical Data

<b>Internal Power Supply</b>	<b>2 x Li-Ion hot-swap rechargeable batteries</b> 99 Wh, up to 90 minutes operating time, each <0.5 kg / 1.1 lbs each
<b>External Power Supply</b>	input voltage 11 - 34 V DC
<b>Power Consumption</b>	typ. 60 W, max. 70 W (without external devices)
<b>Main Dimensions (width x height x depth)</b>	173 mm x 305 mm x 184 mm
<b>Weight</b>	<b>Scanner without battery &lt;6 kg / 13 lbs</b>
<b>Humidity</b>	max. 80 % non condensing @ +31°C
<b>Protection Class</b>	<b>IP64, dust- and splash-proof</b>
<b>Temperature Range Storage / Operation</b> Low Temperature Operation <sup>2)</sup>	-10°C up to +50°C / 0°C up to +40°C: standard operation -20°C: continuous scanning operation if instrument is powered on while internal temperature is at or above 0°C and still air -40°C: scanning operation for about 20 minutes if instrument is powered on while internal temperature is at or above 15°C and still air

2) Insulating the scanner with appropriate material will enable operation at even lower temperatures.



**RIEGL Laser Measurement Systems GmbH** Horn, Austria | [www.riegl.com](http://www.riegl.com)  
**RIEGL USA Inc.** Winter Garden, Florida, USA | [www.rieglusa.com](http://www.rieglusa.com)  
**RIEGL Japan Ltd.** | **RIEGL China Ltd.** | **RIEGL Australia Pty Ltd.** | **RIEGL Canada Inc.** | **RIEGL UK Ltd.**